#### **ARCHIMEDE 15**



DIMENSIONS/WEIGHT	710 mm x 816 mm H195 mm / 180 kg
LOAD CAPACITY / TOWING CAPACITY	7.500 kg / 15.000 kg
LOAD PLAN / LOAD PLAN TILT	Ø155 mm / ± 3°
RANGE	3 h
rear trolleys DIMENSIONS / WEIGHT	300 mm x 380 mm H195 mm / 27 kg each

#### **ARCHIMEDE 30**



DIMENSIONS/WEIGHT	955 mm x 1000 mm H195 mm / 310 kg
LOAD CAPACITY / TOWING CAPACITY	15.000 kg / 30.000 kg
LOAD PLAN / LOAD PLAN TILT	Ø200 mm / ± 3°
RANGE	3 h
rear trolleys DIMENSIONS / WEIGHT	300 mm x 380 mm H195 mm / 27 kg each

#### **ARCHIMEDE 50**

DIMENSIONS/WEIGHT	1330 mm x 1395 mm H215 mm / 590 kg
LOAD CAPACITY / TOWING CAPACITY	25.000 kg / 50.000 kg
LOAD PLAN	Ø200 mm
RANGE	3 h
rear trolleys DIMENSIONS / WEIGHT	300 mm x 390 mm H215 mm / 45 kg each

#### **ARCHIMEDE 100**

DIMENSIONS/WEIGHT	1680 mm x 2080 mm H320 mm / 1700 kg
LOAD CAPACITY / TOWING CAPACITY	50.000 kg / 100.000 kg
LOAD PLAN	Ø280 mm
RANGE	3 h
rear trolleys DIMENSIONS / WEIGHT	570 mm x 620 mm H320 mm / 200 kg each

Via Grieco, 6 - Campogalliano (MO)

+39 059 525751 (3))

info@narosolution.com  $\ \, ext{$igorem{\triangle}$} \,$ 

www.narosolution.com



FOR FURTHER
INFORMATION
CONTACT US!



ARC20250325R1ENG





# ARCHIMEDE



**ARCHIMEDE** IS THE RANGE OF MOTORIZED ELECTRIC TROLLEYS OF THE **NARO SOLUTION**.

DESIGNED TO **OVERCOME** EXPECTATIONS AND **OBSTACLES**THAT USERS HAVE TO FACE
DAILY.



THE BALANCE BETWEEN **SMALL SIZE** AND **POWER** MAKE THEM **ESSENTIAL** FOR **INDOOR** MOVING.


DESIGNED FOR **NARROW SPACES**.

THE **CNC-MACHINED** CHASSIS GUARANTEES **SOLIDITY** AND **PRECISION**.

All information in this document is for guidance only, so it is not binding for legal purposes

# **100% ELECTRIC & INDEPENDENT**

POWER IS SUPPLIED BY LITHIUM BATTERY PACKS. THANKS TO THIS TECHNOLOGY, THE BATTERY DOESN'T NEED TO BE FILLED UP AND DOESN'T SUFFER FROM **MEMORY EFFECT**. RECHARGE CAN BEGIN AT ANY TIME, WITHOUT DAMAGING THE SOH (HEALTH STATUS).



# **MAXIMUM PRODUCTIVITY**

WITHIN MINUTES THE USER IS READY TO START MOVING,

WITH **ARCHIMEDE** THE SETUP PHASE IS MINIMUM:

**TURN THE KEY AND GO!** 

THE **OPERATOR INTERFACE** IS SIMPLE AND INTUITIVE. FEW ESSENTIAL COMMANDS TO BE **SMOOTHLY PRODUCTIVE.** 



5 min

# **SAFETY**

THERE ARE FIVE ANCHORING POINTS ON THE LOADING **PLATE**, WHICH ARE USEFUL TO FIX THE LOAD ON ARCHIMEDE, AVOIDING UNFORESEEN SETBACKS. THE LOAD HEAD TILTS ±3 DEGREES, HELPING TO OVERRIDE ROUGHNESS IN THE FLOOR.

#### **OPTIONAL**

**BRAKED MOTORS** ARE AVAILABLE UPON REQUEST, ENSURING A SAFE PARKING.



# **HIGH QUALITY**

**OUR POLICY INCLUDES** THE USE OF ONLY **FIRST-RATE COMPONENTS**: MOTORS, GEARBOXES, BEARINGS AND ELECTRONICS ARE ALL SOURCED FROM EUROPE.

FROM THE CHOICE OF **METALS**, TO **TYRE COMPOUNDS**, EVERYTHING IS DESIGNED TO ACHIEVE THE BEST RESULT POSSIBLE.

# **POWER & PRECISION**

**POWER** TRANSMISSION STARTS FROM THE **BRUSHLESS MOTOR.** 

THE PLANETARY **GEARBOX** MULTIPLIES THE TORQUE AND, THROUGH A CASCADE OF GEARS, TRANSMITS IT TO THE AXLES. THIS TYPE OF TRANSMISSION GIVES US HIGH PRECISION WHILE MOVING AND THE LEAST LOSS OF POWER.



# **CLEAN ROOM READY**

**ARCHIMEDE** IS ALSO SUITABLE FOR USE IN THE FOOD, PHARMACEUTICAL, AND CHEMICAL INDUSTRIES, **CLEAN ROOMS** AND IN ALL THOSE AREAS WHERE CONTAMINATION OF THE WORKPLACE IS NOT ALLOWED.



# **SERVICE & AFTER SALES**

#### **NARO SOLUTION**

**CUSTOMERS** CAN COUNT ON **OUR TECHNICAL SUPPORT** 

ANYTIME.

WHICH GUARANTEES A

PREMIUM SERVICE,

THANKS TO THE LARGE **SPARE PARTS** WAREHOUSE.

